

**America Specification:**

<b>ENGINE:</b>		
Type		Air-cooled, DOHC, parallel-twin, 270° firing interval
Capacity		865cc
Bore/Stroke		90 x 68mm
Compression Ratio		9.2: 1
Fuel System		Twin carburettors with throttle position sensor and electric carburettor heaters.
Exhaust		Stainless steel headers, twin chrome silencers
Ignition		Digital-inductive type
<b>TRANSMISSION:</b>		
Primary Drive		Gear
Final Drive		X ring chain
Clutch		Wet, multi-plate
Gearbox		5-speed
Throttle body diameter		∅36.8
Gear Ratios		Primary: 108/62 1 <sup>st</sup> : 41/15 2 <sup>nd</sup> : 37/19 3 <sup>rd</sup> : 34/22 4 <sup>th</sup> : 31/24 5 <sup>th</sup> : 29/27 Final: 43/16
Oil Capacity		4.5 litres (1.2 US gals)
<b>CYCLE PARTS:</b>		
Frame		Tubular steel cradle
Swingarm		Twin-sided, tubular steel
Wheels	Front	Cast aluminium alloy 12-spoke 18 x 2.5in
	Rear	Cast aluminium alloy 12-spoke 15 x 3.5in
Tyres	Front	Metzeler Lasertec 110/90 18
	Rear	Metzeler ME880 170/80 15
Suspension	Front	Kayaba, 130mm travel, 41mm forks
	Rear	Kayaba chromed spring twin shocks with adjustable preload, 96mm rear wheel travel
Brakes	Front	Single 310mm disc, Nissin 2 piston floating caliper
	Rear	Single 285mm disc, Nissin 2 piston floating caliper
Instrument display/functions		Analogue speedometer featuring LCD odometer and trip information
<b>DIMENSIONS:</b>		
Length		2420mm (95.2in)
Width (Handlebars)		960mm (37.8in)
Height		1170mm (46.1in)
Seat Height		720mm (28.3in)
Wheelbase		1655mm (65.2in)
Rake/Trail		33.3°/153mm
Weight (Dry)		226kg (497lbs)
Fuel Tank Capacity		19.3 litres (5.1 gal US)

**Triumph Motorcycles Limited**

Normandy Way, Hinckley, Leicestershire, LE10 3BZ United Kingdom  
 Telephone +44 (0)1455 251700, Facsimile +44 (0)1455 453005  
[www.triumphmotorcycles.com](http://www.triumphmotorcycles.com)

---

<b>PERFORMANCE:</b> (MEASURED AT CRANKSHAFT TO DIN 70020)		
Maximum Power		55PS (54bhp/40kW) at 6,750rpm
Maximum Torque		69Nm (51ft.lbf) at 4,800rpm